

ProPRIME

Ultra High Build Primer

PROPRIME is a high build flexible primer filler ideally suited for most plastic and metal substrates. Fast drying coating resulting in an easily sanded surface.

- Easily sanded, super build flexible primer
- Excellent adhesion onto most plastics and metals
- Highly flexible
- Fast drying
- Supplied with 2 nozzles

Suitable substrates

Correctly prepared bare metal & some plastics.
For ultimate adhesion to plastics, ProXL Plastigrip should be applied first.

Application data



2-3 coats @ 60µm



Dust free 8-12 minutes @ 20°C
Touch dry 20-30 minutes @ 20°C
Re-Coat 2 hours @ 20°C

The drying time depends on temperature, air humidity and thickness of the applied coat.



5-10 Minutes



PLASTICOLOR or a coloured topcoat


Application method



Before use, shake the aerosol for 2 minutes and spray a sample area.



Apply in cross coats from a distance of 250mm from object.



After use turn aerosol upside down, press the nozzle for approx. 5 sec and clear valve.



ProPRIME

Ultra High Build Primer

Technical data

Chemical base	Acrylic Resin
Temp resistance	110°C
VOC content	325g/500ml
Coverage	1.75 - 2.0m ²
Storage notes	10 years in appropriate storage (-10°-25°C, relative air humidity of max. 60%)

Environmentally sound:

The products supplied by ProXL are 100% free of heavy metals and the caps and packaging are made of recyclable material.

Disposal:

Completely emptied cans should be put in recycling skips or appropriate container. Cans which are not empty should be disposed off as special refuse.

This application and technical information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively is the responsibility of the user.

