

# Jewel Paints Chlorinated Rubber Paint

## PRODUCTS

Thinner	<b>JAWEL SYNTHETIC THINNER</b>	0-30%
---------	--------------------------------	-------



## DESCRIPTION AND PROPERTIES

- Fast drying and Good drying depth
- Especially suitable for metal structures and concrete
- Great resistance to water, which allows its use in swimming pools.
- This product must be applied in installations that comply with directive 1999/13/EC.

## CHARACTERISTICS OF VINYL PAINT

<b>Appearance</b>	Satin	
<b>Gloss</b>	75-80% at 60°	
<b>Specific weight of the Binder</b>	1,1 kg/l at 20°C	
<b>Solid content (binder)</b>	48-56 % (weight)	36-40 % (volume)
<b>Solid content ready to use (without dilution)</b>	54-59 % (weight)	40-45 % (volume)
<b>VOC ready to use</b>	> 500 g/l - 2004/42/EC - IIA(i)(500)	
<b>Dry film thickness</b>	50-60 microns (2 coats)	
<b>Theoretical yield 1 µm per litre of binder</b>	460-560 m <sup>2</sup> /l	
<b>Theoretical yield 1 µm per litre of mixing without dilution</b>	410-450 m <sup>2</sup> /l	

## APPLICATION



	<b>Application</b>	<b>% thinner (Vol.)</b>	<b>Viscosity - 20°C (Ford Cup 4)</b>	<b>Pressure (BAR)</b>	<b>Product Pressure (BAR)</b>	<b>Nozzle (mm)</b>	<b>Num. of Coats x µm dry</b>	<b>Flash off (min)</b>
	Gravity feed spray gun	25-30%	20"-23"	2-3	---	1,3-1,5	2x30	5' 20°C
	Brush	0%	-	-	-	-	2	5-10'

If the application requires the use of an additive, it should be taken into account in the addition of solvent.

## DRYING

# JAWEL PAINTS (WEST MIDLANDS LTD)

# Jawel Paints Chlorinated Rubber Paint

 TEMPERATURE	 HANDLING	THROUGH DRY
20° C	30'-40'	2h-2h15'

Oven curing is not recommended.

The product reaches its maximum performance after 15 days of drying in the air (ambient temperature 18-22°C).

## REMARKS

- Recommended to be used in ventilated spray booth at 20°C.

## EQUIPMENT CLEANING

- Use a cleaning thinner before the pot life has expired.

## SAFETY

- Follow instructions of product label.
- For more information check the Safety Data Sheet.
- Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

## STORAGE

- Store the product in a ventilated place far from direct exposure to sunlight.
- Keep between +5°C and +30°C.

*These products are for professional use only. The Safety Data Sheet should be consulted before use and the precautionary warnings on the product packaging should be observed. Its correct use, according to its purpose and respecting its technical and security data, provided in these documents, is the sole and exclusive responsibility of the user. Jawel Paints declines any liability due to the incorrect use of any product.*

*The information included in this documentation is based on our scientific and technical knowledge on the date of its issuance. Jawel Paints reserves the right to modify and/or discontinue all or part of the information at any time and without prior notice. It is the user's responsibility to verify the update of the information. The latest version of this document replaces all previous versions.*

*All clauses contained herein apply to any future changes or modifications.*

*For any additional technical information please consult with our Customer Service or our Technical Department.*