

Jewel Paints Canvas Vinyl Paint

1k Acrylic Single Stage for Tarpaulings and Awnings

PRODUCTS

Thinner	JAWEL SYNTHETIC THINNER	50-60%
---------	--------------------------------	--------

DESCRIPTION AND PROPERTIES

- Monocomponent acrylic paint.
- Very flexible, especially for tarpaulings and awnings.
- Semi bright appearance.
- Very rapid drying.

CHARACTERISTICS OF VINYL PAINT

Appearance	Glossy	
Gloss	>70 at 60°	
Specific weight of the Binder	0,9 kg/l at 20°C	
Solid content (binder)	28-32 % (weight)	24-28 % (volume)
Solid content ready to use (without dilution)	36-41 % (weight)	29-34 % (volume)
VOC ready to use	> 500 g/l - 2004/42/EC - IIA(i)(500)	
Dry film thickness	30 microns (1 coats)	
Theoretical yield 1 µm per litre of binder	320-420 m ² /l	
Theoretical yield 1 µm per litre of mixing without dilution	260-360 m ² /l	

SUBSTRATE AND PREPARATION OF THE SURFACE


	CLEANING	SANDING	FINAL CLEANING
Tarpaulings/Awnings	Jewel Panel Wipe	---	---

JAWEL PAINTS (WEST MIDLANDS LTD)

Jewel Paints Canvas Vinyl Paint



1k Acrylic Single Stage for Tarpaulings and Awnings

APPLICATION

	Application	% thinner (Vol.)	Viscosity - 20°C (Ford Cup 4)	Pressure (BAR)	Product Pressure (BAR)	Nozzle (mm)	Num. of Coats x µm dry	Flash off (min)
	Gravity feed spray gun	50-60%	15"-17"	2-3	---	1,3-1,5	1x30	5' 20°C

If the application requires the use of an additive, it should be taken into account in the addition of solvent.

DRYING

 TEMPERATURE	 HANDLING	THROUGH DRY
20° C	10'-15'	15'-20'

Oven curing is not recommended.

The product reaches its maximum performance after 15 days of drying in the air (ambient temperature 18-22°C).

REMARKS

- Recommended to be used in ventilated spray booth at 20°C.
- Jewel Canvas and Vinyl is a painting adhesive for multiple types of canvas. However it is recommended that a test is carried out to check the correct adhesion.
- It is important to apply the recommended thickness to obtain the best results.

Jawel Paints Canvas Vinyl Paint

1k Acrylic Single Stage for Tarpaulings and Awnings

EQUIPMENT CLEANING

- Use a cleaning thinner before the pot life has expired.

SAFETY

- Follow instructions of product label.
- For more information check the Safety Data Sheet.
- Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

STORAGE

- Store the product in a ventilated place far from direct exposure to sunlight.
- Keep between +5°C and +30°C.

These products are for professional use only. The Safety Data Sheet should be consulted before use and the precautionary warnings on the product packaging should be observed. Its correct use, according to its purpose and respecting its technical and security data, provided in these documents, is the sole and exclusive responsibility of the user. Jawel Paints declines any liability due to the incorrect use of any product.

The information included in this documentation is based on our scientific and technical knowledge on the date of its issuance. Jawel Paints reserves the right to modify and/or discontinue all or part of the information at any time and without prior notice. It is the user's responsibility to verify the update of the information. The latest version of this document replaces all previous versions.

All clauses contained herein apply to any future changes or modifications.

For any additional technical information please consult with our Customer Service or our Technical Department.

JAWEL PAINTS (WEST MIDLANDS LTD)