


## Evolve Range

Date: 25-01-2019

Page: 1

### DESCRIPTION

Special FX Evolve Range is a special Colour Changing paint that has been specifically developed to ensure a great colour change from one colour to another when viewed at different angles. For best results use Special FX Deep Black Basecoat as an undercoat followed by applying the Evolve colour changing paint.



**Mix Ratio**  
100:50

Mix by volume, 2 parts of Special FX Evolve Solvent basecoat to 1 part basecoat thinner. This gives a bright and quick coverage application. A mixing ratio of 1:1 may be used but will alter the covering power.




**Spraying viscosity**  
16-18 s (DIN4/20°C)



**Spraygun tips**  
1.2-1.3 mm - 2 bar/32 psi at the air inlet. For best results RP or HTE spray guns should be used.



**Number of coats:**  
Apply 2-3 coats for normal coverage



**Flash off time**  
Between coats: 3-4 min (until matt)  
Before Clearcoat: 10-15 min

### GENERAL NOTES

Colour checking: Colour checking is required before painting of all colours.

### IMPORTANT NOTES

Evolve colour changing paint is hard to apply to a large area. Please try a test panel or make sure the spray gun is setup correctly to ensure no stripy or patchy finish occurs.

Colour name	Colour Effect
Autumn Flash	Green to Red
Liquid Lava	Violet to Orange
Sunrise Gold	Red to Gold

The technical data contained herein is based on our present knowledge and we experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.