

Jawel Force 8 Cellulose

A high quality Cellulose product for use on Classic Cars, Industrial applications. It gives excellent gloss 'from the gun' and provides fast through drying, ease of use, and gives a hard and durable dried film enabling rapid throughput of work.

References

Technical Properties

Coverage

20 square metres per litre @ 20 microns dft

Flashpoint

4 °C

Temperature Resistance

Up to 80 °C

Storage

Store between 5°C - 25°C. When not in use, cans must be kept sealed

Shelf Life

12 months from delivery date in original sealed containers

Maximum VOC Content

0.70 Kg/l

Regulations

For use in Aerosol, Classic Car Refinish and Industrial Applications

Not to be used in connection with 2004/42/CE

Not to be Used under SI2005:27773

Colour Range

Available in a wide colour range including RAL & BS & Classic Car shades.

Cleaning

Ensure surfaces to be coated are dry and must be cleaned using the appropriate product to remove all traces of contaminants. Jewel produce a full range of Preparatory Cleaners suitable for most cleaning and degreasing processes. Over Wood: Fill grain as appropriate using good quality wood filler. Flat thoroughly using 180 - 240 Garnet Paper. Tack rag surface. Apply Spirit Stain if appropriate. Sanding Sealer or Pre-Cat Sanding Basecoat are used on woods subject to grain raising prior to application of Industrial cellulose lacquers. Pre-treatment: Under 'pigmented' Industrial Cellulose colours on wood and on steel substrates a variety of Build Up systems can be used. NB: If Jewel FORCE 8 cellulose is to be used over aluminium and alloys an etch primer or Washfiller must be used.

Health & Safety

- Refer to SDS and tin label prior to use.

Issued

22/09/2005 16:35:00