

Jawel Paints Ltd

SAFETY DATA SHEET 2 K Thinner

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 2 K Thinner
Product number S152
Internal identification SWS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses PC9a: Coatings and paints, thinners, paint removers.
Uses advised against Use only for intended applications.

1.3. Details of the supplier of the safety data sheet

Supplier Jawel Paints(West Midlands) Ltd
313-317 Heath Street
Smethwick
West Midlands
B66 2QY
Telephone: 0121 558 6191

1.4. Emergency telephone number

Emergency telephone 0844 5605341 (24 Hours) (in use from 13/01/13)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226
Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315 STOT SE 3 - H336
Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Warning

2 K Thinner

Hazard statements	H226 Flammable liquid and vapour. H315 Causes skin irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness.
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapour/ spray. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P314 Get medical advice/ attention if you feel unwell. P403+P235 Store in a well-ventilated place. Keep cool.
Contains	XYLENE, BUTYL ACETATE -norm, 1-METHOXY-2-PROPANOL
Supplementary precautionary statements	P240 Ground/ bond container and receiving equipment. P241 Use explosion-proof electrical equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P302+P352 IF ON SKIN: Wash with plenty of water. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P332+P313 If skin irritation occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

BUTYL ACETATE -norm		20-40%
CAS number: 123-86-4	EC number: 204-658-1	REACH registration number: 01-2119485493-29-XXXX
Classification		
Flam. Liq. 3 - H226 STOT SE 3 - H336		
Xylene		20-40%
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-XXXX
Classification		
Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315		

2 K Thinner

2-METHOXY-1-METHYLETHYL ACETATE	10-20%
CAS number: 108-65-6	EC number: 203-603-9
Classification	
Flam. Liq. 3 - H226	
1-METHOXY-2-PROPANOL	10-20%
CAS number: 107-98-2	EC number: 203-539-1
Classification	
Flam. Liq. 3 - H226 STOT SE 3 - H336	Classification (67/548/EEC or 1999/45/EC) R10 R67

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Remove casualty from exposure ensuring one's own safety whilst doing so. If inhaled remove person to fresh air and keep comfortable for breathing.
Ingestion	Do not induce vomiting. If conscious give 500ml of water to drink immediately. Wash out mouth with water. Consult a doctor.
Skin contact	Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash skin thoroughly with soap and water. If irritation occurs get medical advice/attention.
Eye contact	If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Transfer to hospital for specialist examination.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	There may be irritation of the throat with a feeling of tightness in the chest.
Ingestion	There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.
Skin contact	There may be irritation and redness at the site of contact.
Eye contact	There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	If exposed or concerned get medical advice/attention.
Specific treatments	Eye bathing equipment should be available on the premises.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. Carbon dioxide (CO ₂). Carbon monoxide (CO).
--------------------------------------	---

2 K Thinner

5.3. Advice for firefighters

Special protective equipment for firefighters Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid. Take precautionary measures against static discharge.

For non-emergency personnel Follow instructions given by emergency personnel.

For emergency responders Refer to this MSDS.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Contain the spillage using bunding. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Use only non-sparking tools.

6.4. Reference to other sections

Reference to other sections See Section 1 for emergency contact information. For personal protection, see Section 8. Collect and dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation of mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting. Do not breathe mist/vapours/spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep container tightly closed. Use only non-sparking tools.

Advice on general occupational hygiene Take off contaminated clothing and wash it before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

2 K Thinner

Xylene

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m³(Sk)

2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 274 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 548 mg/m³(Sk)

1-METHOXY-2-PROPANOL

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 375 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 560 mg/m³(Sk)

WEL = Workplace Exposure Limit

DNEL No data available.

PNEC No data available.

BUTYL ACETATE -norm (CAS: 123-86-4)

Ingredient comments	WEL = Workplace Exposure Limits
DNEL	Industry - Inhalation; Long term : 310 mg/m ³
PNEC	Industry - Fresh water; Long term 0.4 mg/l Industry - Marine water; Long term 0.04 mg/l

Xylene (CAS: 1330-20-7)

Ingredient comments	WEL = Workplace Exposure Limits
DNEL	No data available.
PNEC	No data available.

8.2. Exposure controls

Protective equipment

Appropriate engineering controls	Ensure there is sufficient ventilation of the area. Use explosion-proof electrical/ventilating/lighting. Take precautionary measures against static discharge.
Eye/face protection	Tightly fitting safety goggles. Ensure eye bath is to hand.
Hand protection	Wear protective gloves.
Other skin and body protection	Wear protective clothing. Take precautionary measures against static discharge.
Respiratory protection	Self-contained breathing apparatus must be available in case of emergency.
Environmental exposure controls	Prevent from entering in public sewers or the immediate environment.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Colourless liquid.
Odour	Unpleasant.
Odour threshold	Data lacking.

2 K Thinner

pH	Data lacking.
Melting point	Data lacking.
Initial boiling point and range	Data lacking.
Flash point	Data lacking.
Evaporation rate	Data lacking.
Evaporation factor	Data lacking.
Flammability (solid, gas)	Data lacking.
Upper/lower flammability or explosive limits	Data lacking.
Other flammability	Data lacking.
Vapour pressure	Data lacking.
Vapour density	Data lacking.
Relative density	Data lacking.
Bulk density	Data lacking.
Solubility(ies)	Data lacking.
Partition coefficient	Data lacking.
Auto-ignition temperature	Data lacking.
Decomposition Temperature	Data lacking.
Viscosity	Data lacking.
Explosive properties	Data lacking.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not available.

9.2. Other information

Volatile organic compound This product contains a maximum VOC content of 835 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Stable under recommended transport or storage conditions.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Under normal conditions of storage and use, no hazardous reactions will occur. Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid Avoid heat.

10.5. Incompatible materials

Materials to avoid Strong acids. Strong oxidising agents.

2 K Thinner

10.6. Hazardous decomposition products

Hazardous decomposition products In combustion emits toxic fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 3,666.67

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Harmful if inhaled.

ATE inhalation (gases ppm) 15,000.0

ATE inhalation (vapours mg/l) 36.67

ATE inhalation (dusts/mists mg/l) 5.0

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Not sensitising.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Does not contain any substances known to be mutagenic.

Genotoxicity - in vivo Does not contain any substances known to be mutagenic.

Carcinogenicity

Carcinogenicity There is no evidence that the product can cause cancer.

Reproductive toxicity

Reproductive toxicity - fertility Does not contain any substances known to be toxic to reproduction.

Reproductive toxicity - development This substance has no evidence of toxicity to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure.

2 K Thinner

Inhalation	There may be irritation of the throat with a feeling of tightness in the chest.
Ingestion	There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.
Skin contact	There may be irritation or redness at the site of contact.
Eye contact	There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.
Route of entry	Inhalation Ingestion Skin and/or eye contact

Toxicological information on ingredients.

BUTYL ACETATE -norm

Toxicological effects	No information available.
Other health effects	There is no evidence that the product can cause cancer.
<u>Acute toxicity - oral</u>	
Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
<u>Acute toxicity - dermal</u>	
Notes (dermal LD₅₀)	Based on available data the classification criteria are not met.
<u>Acute toxicity - inhalation</u>	
Notes (inhalation LC₅₀)	Based on available data the classification criteria are not met.
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Not irritating.
Animal data	Not irritating.
Human skin model test	Data lacking.
Extreme pH	Data lacking.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Not irritating to eyes
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Not sensitising.
<u>Skin sensitisation</u>	
Skin sensitisation	Not sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	This substance has no evidence of mutagenic properties.
Genotoxicity - in vivo	This substance has no evidence of mutagenic properties.
<u>Carcinogenicity</u>	
Carcinogenicity	There is no evidence that the product can cause cancer.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	This substance has no evidence of toxicity to reproduction.

2 K Thinner

Reproductive toxicity - development	This substance has no evidence of toxicity to reproduction.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
<u>Aspiration hazard</u>	
Aspiration hazard	Not anticipated to present an aspiration hazard, based on chemical structure.
<u>General information</u>	
General information	No specific health hazards known.
Inhalation	Drowsiness, dizziness, disorientation, vertigo.
Ingestion	No specific health hazards known.
Skin contact	Prolonged contact may cause dryness of the skin.
Eye contact	The eyes may water profusely.
Acute and chronic health hazards	Gas or vapour in high concentrations may irritate the respiratory system.
Route of entry	Inhalation Ingestion Skin and/or eye contact
Target organs	Central nervous system Eyes Liver Respiratory system, lungs Skin
Medical considerations	Chronic respiratory and obstructive airway diseases. Skin disorders and allergies. Liver and/or kidney damage. Convulsions. Central nervous system depression.
<u>Xylene</u>	
Toxicological effects	No information available.
Other health effects	There is no evidence that the product can cause cancer.
<u>Acute toxicity - oral</u>	
Notes (oral LD₅₀)	Based on available data the classification criteria are not met.
<u>Acute toxicity - dermal</u>	
Notes (dermal LD₅₀)	Harmful in contact with skin.
<u>Acute toxicity - inhalation</u>	
Notes (inhalation LC₅₀)	Harmful if inhaled.
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Irritating to skin.
Animal data	Data lacking.
Human skin model test	Data lacking.
Extreme pH	Data lacking.
<u>Serious eye damage/irritation</u>	

2 K Thinner

Serious eye damage/irritation	Not irritating to eyes
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Not sensitising.
<u>Skin sensitisation</u>	
Skin sensitisation	Not sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	This substance has no evidence of mutagenic properties.
Genotoxicity - in vivo	This substance has no evidence of mutagenic properties.
<u>Carcinogenicity</u>	
Carcinogenicity	There is no evidence that the product can cause cancer.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	This substance has no evidence of toxicity to reproduction.
Reproductive toxicity - development	Does not contain any substances known to be toxic to reproduction.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Not classified as a specific target organ toxicant after a single exposure.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
<u>Aspiration hazard</u>	
Aspiration hazard	Not anticipated to present an aspiration hazard, based on chemical structure.
<u>General information</u>	
General information	No specific health hazards known.
Inhalation	There may be irritation of the throat with a feeling of tightness in the chest.
Ingestion	There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.
Skin contact	There may be irritation or redness at the site of contact.
Eye contact	There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred.
Acute and chronic health hazards	This product may cause skin and eye irritation. Symptoms following overexposure may include the following: Irritation of eyes and mucous membranes. Toxic through skin absorption (percutaneous). A single exposure may cause the following adverse effects: Central nervous system depression. Anaesthetic in high concentrations. Repeated exposure may cause chronic eye irritation. Acute eczematous dermatitis, contact type erythema, oedema, papules, vesicles, bullae, crusts, desquamation. Swallowing concentrated chemical may cause severe internal injury. Unconsciousness. Death.
Route of entry	Inhalation Skin absorption Ingestion. Skin and/or eye contact

2 K Thinner

Target organs	Blood Central nervous system Eyes Gastro-intestinal tract Kidneys Liver Respiratory system, lungs Skin
Medical symptoms	Severe irritation, burning and tearing. Dilated pupils. Rhinitis (inflammation of the nasal mucous membranes). Upper respiratory irritation. General respiratory distress, unproductive cough. May cause suffocation. Severe skin irritation. Nausea, vomiting. Unconsciousness, possibly death. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Behavioural changes. Hypotension (low blood pressure). Dizziness.
Medical considerations	Skin disorders and allergies. Convulsions. Central nervous system depression.

SECTION 12: Ecological Information

Ecotoxicity The product is not expected to be hazardous to the environment.

Ecological information on ingredients.

BUTYL ACETATE -norm

Ecotoxicity The product is not expected to be hazardous to the environment.

Xylene

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

Ecological information on ingredients.

BUTYL ACETATE -norm

Toxicity	Not considered toxic to fish.
Acute toxicity - fish	LC ₅₀ , 96 hours: 100 mg/l, Algae
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 44-205 mg/l, Daphnia magna
Acute toxicity - aquatic plants	Not available.
Acute toxicity - microorganisms	Not available.
Acute toxicity - terrestrial	Not available.
Chronic toxicity - fish early life stage	Not available.
Short term toxicity - embryo and sac fry stages	Not available.
Chronic toxicity - aquatic invertebrates	Not available.

Xylene

Toxicity	Not considered toxic to fish.
Acute toxicity - fish	LC ₅₀ , 96 hours: 1430 mg/l, Algae

2 K Thinner

Acute toxicity - aquatic invertebrates	Not available.
Acute toxicity - aquatic plants	Not available.
Acute toxicity - microorganisms	Not available.
Acute toxicity - terrestrial	Not available.
Chronic toxicity - fish early life stage	Not available.
Short term toxicity - embryo and sac fry stages	Not available.
Chronic toxicity - aquatic invertebrates	Not available.

1-METHOXY-2-PROPANOL

Toxicity	LOW
-----------------	-----

12.2. Persistence and degradability

Persistence and degradability No data available.

Ecological information on ingredients.

BUTYL ACETATE -norm

Persistence and degradability	The degradability of the product is not known.
--------------------------------------	--

Xylene

Persistence and degradability	No data available.
--------------------------------------	--------------------

1-METHOXY-2-PROPANOL

Persistence and degradability	RAPID.
--------------------------------------	--------

12.3. Bioaccumulative potential

Bioaccumulative potential Data lacking.

Partition coefficient Data lacking.

Ecological information on ingredients.

BUTYL ACETATE -norm

Bioaccumulative potential	The product is not bioaccumulating.
Partition coefficient	Data lacking.

Xylene

2 K Thinner

Bioaccumulative potential Data lacking.

Partition coefficient Data lacking.

1-METHOXY-2-PROPANOL

Bioaccumulative potential LOW

12.4. Mobility in soil

Mobility Readily absorbed into soil

Ecological information on ingredients.

BUTYL ACETATE -norm

Mobility No data available.

Adsorption/desorption coefficient Data lacking.

Henry's law constant Data lacking.

Surface tension Data lacking.

Xylene

Mobility Readily absorbed into soil

Adsorption/desorption coefficient Data lacking.

Henry's law constant Data lacking.

Surface tension Data lacking.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

BUTYL ACETATE -norm

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

Xylene

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Negligible ecotoxicity

Ecological information on ingredients.

BUTYL ACETATE -norm

Other adverse effects Not available.

2 K Thinner

Xylene

Other adverse effects Negligible ecotoxicity

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Avoid release to the environment.
Disposal methods	Transfer to a suitable container and arrange for collection by specialised disposal company. NB the user's attention is drawn to the possible existence of regional or national regulations regarding disposal.
Waste class	08 01 11

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263
UN No. (ADN)	1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PAINT RELATED MATERIAL
Proper shipping name (IMDG)	PAINT RELATED MATERIAL
Proper shipping name (ICAO)	PAINT RELATED MATERIAL
Proper shipping name (ADN)	PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

2 K Thinner

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3Y
Hazard Identification Number (ADR/RID)	30
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Not applicable

15.2. Chemical safety assessment

A REACH chemical safety assessment has been carried out on the REACH registered products showing in section 3 of SDS

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	ATE: Acute Toxicity Estimate. DNEL: Derived No Effect Level. PNEC: Predicted No Effect Concentration. CLP: Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] EUH statement: CLP-specific Hazard statement
General information	This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.
Revision comments	Product name change.
Issued by	Nicola Dobson, Technical Services Supervisor
Revision date	13/02/2018
Revision	14
Supersedes date	03/01/2018
SDS number	20897
SDS status	Approved.
Hazard statements in full	H226 Flammable liquid and vapour. H312 Harmful in contact with skin. H315 Causes skin irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness.
Signature	N Dobson

2 K Thinner

The above information is believed to be correct but does not purport to be all inclusive and shall be used as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.