

PANELWIPE DATA SHEET

Page 1 Issued: 22/11/2005 Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: PANELWIPE

Part number: PANELWIPE

Company name:

Jawel Paints (West Midlands)Ltd Units 313-317 Heath Street Smethwick

West Midlands B66 2QY Tel: 0121-558-6193

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED LIGHT >90% EINECS: 265-151-9 CAS: 64742-49-0

[F+] R12; [Xi] R38; [N] R51/53; [Xn] R65

3. HAZARDS IDENTIFICATION

Main hazards: Highly flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment. Harmful: may cause lung damage if swallowed.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.
Eye contact: There may be irritation and redness. The eyes may water profusely.
Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.
Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

SAFETY DATA SHEET

PANELWIPE 3

5. FIRE-FIGHTING MEASURES			
Extinguishing media:	Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool		
	containers.		
Exposure hazards:	Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour		
L.	may travel considerable distance to source of ignition and flash back.		
Protection of fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin		
	and eyes.		
6. ACCIDENTAL RELEASE MEASURES			
Personal precautions:	Refer to section 8 of SDS for personal protection details. If outside do not approach from		
- or some proceedings	downwind. If outside keep bystanders upwind and away from danger point. Mark out the		
	contaminated area with signs and prevent access to unauthorised personnel. Turn leaking		
	containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.		
Environmental precautions:	Do not discharge into drains or rivers. Contain the spillage using bunding.		
Clean-up procedures:	Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by		
	an appropriate method. Do not use equipment in clean-up procedure which may produce		
	sparks.		
7. HANDLING AND STORAGE			
Handling requirements:	Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do		
<i>.</i>	not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is		
	forbidden. Use non-sparking tools.		
Storage conditions:	Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of		
	ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and		
	electrical equipment are not a source of ignition.		
8. EXPOSURE CONTROLS	8. EXPOSURE CONTROLS / PERSONAL PROTECTION		
Engineering measures:	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not		
	a source of ignition.		
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.		
Hand protection:	Impermeable gloves.		
Eye protection:	Safety glasses. Ensure eye bath is to hand.		
Skin protection:	Impermeable protective clothing.		
9. PHYSICAL AND CHEMIC	9. PHYSICAL AND CHEMICAL PROPERTIES		

State: Liquid

Flash point°C: 2

SAFETY DATA SHEET

PANELWIPE 3

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature.

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility:	Readily absorbed into soil.
Persistence and degradability:	Biodegradable.
Bioaccumulative potential:	No bioaccumulation potential.
Other adverse effects:	Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

14. TRANSPORT INFORMATION

UN no:	3295 ADR Class	: 3
Packing group:	II Classification code	: F1
Shipping name:	HYDROCARBONS, LIQUID, N.O.S.	
Labelling:	3 Hazard ID no	: 33
	TLANYAGLE LOUIS	
IMDG / IMO		
UN no:	3295 Class	: 3
Packing group:	II Ems	: F-E,S-D
	Labelling	• 3
Marine pollutant:	. Easting	• 5
Marine pollutant: IATA / ICAO		• 5
IATA / ICAO	3295 Class	

Page 3

SAFETY DATA SHEET

PANELWIPE 3

Page 4

15. REGULATORY INFORMATION Hazard symbols: Highly flammable. Dangerous for the environment. Harmful. R11: Highly flammable. **Risk phrases:** R38: Irritating to skin. R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65: Harmful: may cause lung damage if swallowed. Safety phrases: S9: Keep container in a well-ventilated place. S16: Keep away from sources of ignition - No smoking. S33: Take precautionary measures against static discharges. S61: Avoid release to the environment. Refer to special instructions / safety data sheets. S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions. **16. OTHER INFORMATION** Risk phrases used in s.2: R12: Extremely flammable. R38: Irritating to skin. R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.